

SCHEDA TECNICA/ TECHNICAL SHEET

TESSUTO CAT. 2 VAR. 361 --> 378

	METODO Method	VALORI Value
COMPOSIZIONI (composition)		100% PL
ALTEZZA (width)		140 cm
PESO (weight)		560 +/- 5% gr/mq
RESISTENZA ALL' ABRASIONE (abrasion resistance) MARTINDALE	UNI EN ISO 12947-1	50.000 giri
RESISTENZA AL PILLING (pilling resistance)	UNI EN ISO 12945-2	5
SOLIDITÀ ALLA LUCE (colourfastness to light)	UNI EN ISO 105-B02	4
SOLIDITÀ ALLO SFREGAMENTO (colourfastness to crocking) – SECCO (dry) – UMIDO (wet)	UNI EN ISO 105 X12	4 4

STABILITÀ DI LAVAGGIO (dimensional stability)	Trama / weft %	Ordito / warp %
SECCO (dry)	0	0
ACQUA (washing)	0	0

MANUTENZIONE (cleaning)
 

NOTE

STAIN RESISTANT

Wine, sugary drinks, spirits, liqueurs, beer, coffee, tea, milk: the fabric is subjected to a stain-resistant treatment which protects from liquids, for this reason it is sufficient to remove these substances with a damp cloth. Ballpoint pen, chewing gum, resin, chocolate, candy: rub the stain with a cloth soaked in 90% ethyl alcohol.

Grease, oil, cosmetics: Use the foam of a neutral soap to remove the stain, then remove the soap with a damp cloth.

The surface of this item may experience color transfer due to some dyes used for clothing and accessories (e.g. jeans). This aspect is amplified with high humidity or high temperatures. The company isn't responsible in case of color migration.